



Figure similar

SIPLUS HMI KP8 PN based on 6AV3688-3AY36-0AX0 with conformal coating, -40...+60 °C, start up -25 °C,

General information	
Product type designation	KP8 PN
based on	6AV3688-3AY36-0AX0
Control elements	
With parameterizable keys	Yes
Keyboard	
<ul style="list-style-type: none"> Membrane keyboard <ul style="list-style-type: none"> — user-definable label membrane keys Function keys <ul style="list-style-type: none"> — Number of function keys Short-stroke keys <ul style="list-style-type: none"> — Number of short-stroke keys 	Yes 8 8
Expansions for operator control of the process	
<ul style="list-style-type: none"> DP direct LEDs (LEDs as S7 output I/O) Number of color modes for LED Direct keys (keys as S7 input I/O) 	8; Adjustable brightness 5; red, green, blue, yellow, white 8
Installation type/mounting	
Mounting type	Mounting clip
Mounting position	vertical
Rack mounting	No
Front mounting	Yes; Compatible with Extension Units dimensions
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Number of slots for command devices and signaling units	0
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; 24 V looped through at connector, no interruption on pulling
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.3 A
Digital inputs	
Number of digital inputs	8; Max. 8 inputs and outputs (total)
Input voltage	

• Rated value (DC)	24 V
Digital outputs	
Number of digital outputs	8; Max. 8 inputs and outputs (total)
Short-circuit protection	Yes
Switching capacity of the outputs	
• with resistive load, max.	100 mA
Output voltage	
• Rated value (DC)	24 V; Non-isolated
Total current of the outputs	
• Current per channel, max.	100 mA
• Current per group, max.	800 mA
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	
• Industrial Ethernet status LED	2; Per port
• Number of ports of the integrated switch	2; Per port
Protocols	
PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
PROFIsafe	No
PROFIBUS	No
EtherNet/IP	No
MPI	No
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
• TCP/IP	No
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
• AS-Interface Safety at Work	No
• CAN	No
• Data-Highway	No
• DeviceNet	No
• DeviceNet Safety	No
• Foundation Fieldbus	No
• INTERBUS	No
• INTERBUS-Safety	No
• Local Operating Network	No
• MODBUS	No
• SafetyBUS p	No
• SERCOS	No
• SUCOnet	No
• other bus systems	No
Test commissioning functions	
Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; Group 1, measured at a distance of 10 m
• Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	

• Enclosure Type 4 at the front	No
• Enclosure Type 4x at the front	Yes; Incl. NEMA12
Standards, approvals, certificates	
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C; = Tmin; Startup @ -25 °C
• max.	60 °C; = Tmax
Operation (vertical installation)	
— For vertical installation, min.	-40 °C; = Tmin; Startup @ -25 °C
— For vertical installation, max.	60 °C; = Tmax
Operation (max. tilt angle)	
— At maximum tilt angle, min.	-40 °C; = Tmin; Startup @ -25 °C
— At maximum tilt angle, max.	45 °C; = Tmax
Operation (vertical installation, portrait format)	
— For vertical installation, min.	-40 °C; = Tmin; Startup @ -25 °C
— For vertical installation, max.	60 °C; = Tmax
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	-40 °C; = Tmin; Startup @ -25 °C
— At maximum tilt angle, max.	45 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-25 °C
• max.	80 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection

- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Discoloration of coating possible during service life

Yes; Conformal coating, Class A

Configuration

Configuration software

- STEP 7 Basic (TIA Portal) Yes
- STEP 7 Professional (TIA Portal) Yes

Functionality under WinCC (TIA Portal)

Process coupling

- S7-1200 Yes; with ET 200pro CPU and ET 200S CPU
- S7-1500 Yes
- S7-200 No
- S7-300/400 Yes; with F-CPU: STEP 7 V11 SP1 (or higher) and Safety V11 (or higher) or SIMATIC STEP 7 Basic V11 (or higher)
- LOGO! No
- WinAC Yes
- SINUMERIK No
- SIMOTION No
- Allen Bradley (EtherNet/IP) No
- Allen Bradley (DF1) No
- Mitsubishi (MC TCP/IP) No
- Mitsubishi (FX) No
- OMRON (FINS TCP) No
- OMRON (Host Link) No
- Modicon (Modbus TCP/IP) No
- Modicon (Modbus RTU) No

Mechanics/material

- Enclosure material (front)
 - Plastic Yes
 - Aluminum No
 - Stainless steel No

Service life

- Short-stroke keys (in switching cycles) 1 500 000
- LEDs (ON period) 100 %

Dimensions

- Width of the housing front 98 mm
- Height of housing front 155 mm
- Mounting cutout, width 68 mm; Max. thickness of mounting plate 2 - 6 mm
- Mounting cutout, height 129 mm
- mounting depth 49 mm; Incl. angled SIMATIC Ethernet connector

Weights

- Weight (without packaging) 280 g

Classifications

	Version	Classification
eClass	16	27-33-02-04
eClass	14	27-33-02-04
eClass	12	27-33-02-04
eClass	9.1	27-33-02-04
eClass	9	27-33-02-04
eClass	8	27-24-23-05
eClass	7.1	27-24-23-05
eClass	6	27-24-23-05
ETIM	10	EC001415
ETIM	9	EC001415
ETIM	8	EC001415
ETIM	7	EC001415

IDEA	4	5266
UNSPSC	15	39-12-22-21

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)


[China RoHS](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------

[China RoHS](#)





last modified:
7/28/2025