

SIMATIC S7-1200, Digital output SM 1222, 8 DO, Relay Changeover contact

General information	
Product type designation	SM 1222, DQ 8x relay/2 A
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	140 mA
Digital outputs	
• from load voltage L+, max.	16.7 mA/relay coil
Power loss	
Power loss, typ.	5 W
Digital outputs	
Number of digital outputs	8
• in groups of	1
Short-circuit protection	No; to be provided externally
Switching capacity of the outputs	
• with resistive load, max.	2 A
• on lamp load, max.	30 W with DC, 200 W with AC
Output voltage	
• Rated value (DC)	5 V DC to 30 V DC
• Rated value (AC)	5 V AC to 250 V AC
Output current	
• for signal "1" rated value	2 A
Output delay with resistive load	
• "0" to "1", max.	10 ms
• "1" to "0", max.	10 ms
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	2 A; Current per mass
Relay outputs	
• Number of relay outputs	8
• Rated supply voltage of relay coil L+ (DC)	24 V
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
Switching capacity of contacts	
— with inductive load, max.	2 A
— on lamp load, max.	30 W with DC, 200 W with AC
— with resistive load, max.	2 A
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• for status of the outputs	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Relays
• between the channels, in groups of	1
• between the channels and backplane bus	1 500 V AC for 1 minute

Permissible potential difference			
between different circuits	750 V AC for 1 minute		
Degree and class of protection			
IP degree of protection	IP20		
Standards, approvals, certificates			
CE mark	Yes		
CSA approval	Yes		
UL approval	Yes		
cULus	Yes		
FM approval	Yes		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
Marine approval	Yes		
Ecological footprint			
<ul style="list-style-type: none">environmental product declaration	Yes		
Global warming potential			
<ul style="list-style-type: none">global warming potential, (total) [CO2 eq]	68.6 kg		
<ul style="list-style-type: none">global warming potential, (during production) [CO2 eq]	8.16 kg		
<ul style="list-style-type: none">global warming potential, (during operation) [CO2 eq]	60.7 kg		
<ul style="list-style-type: none">global warming potential, (after end of life cycle) [CO2 eq]	-0.334 kg		
Ambient conditions			
Free fall			
<ul style="list-style-type: none">Fall height, max.	0.3 m; five times, in product package		
Ambient temperature during operation			
<ul style="list-style-type: none">min.	-20 °C		
<ul style="list-style-type: none">max.	60 °C; Number of simultaneously activated outputs: 4 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 8 at 55 °C horizontal or 45 °C vertical		
<ul style="list-style-type: none">horizontal installation, min.	-20 °C		
<ul style="list-style-type: none">horizontal installation, max.	60 °C		
<ul style="list-style-type: none">vertical installation, min.	-20 °C		
<ul style="list-style-type: none">vertical installation, max.	50 °C		
<ul style="list-style-type: none">permissible temperature change	5°C to 55°C, 3°C / minute		
Ambient temperature during storage/transportation			
<ul style="list-style-type: none">min.	-40 °C		
<ul style="list-style-type: none">max.	70 °C		
Air pressure acc. to IEC 60068-2-13			
<ul style="list-style-type: none">Storage/transport, min.	660 hPa		
<ul style="list-style-type: none">Storage/transport, max.	1 080 hPa		
Relative humidity			
<ul style="list-style-type: none">Operation at 25 °C without condensation, max.	95 %		
Connection method			
required front connector	Yes		
Mechanics/material			
Enclosure material (front)			
<ul style="list-style-type: none">plastic	Yes		
Dimensions			
Width	70 mm		
Height	100 mm		
Depth	75 mm		
Weights			
Weight, approx.	310 g		
Classifications			
		Version	Classification
	eClass	16	27-24-22-04
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04

eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



General Product Approval

EMV

For use in hazardous locations

Maritime application

[China RoHS](#)
[Manufacturer Declaration](#)


[EM](#)


Maritime application

Environment

[NK / Nippon Kaiji Kyokai](#)

[KR \(Korean Register of Shipping\)](#)


last modified:

7/2/2025 