SIEMENS

Data sheet 6ES7360-3AA01-0AA0



Figure similar

spare part SIMATIC S7-300, connection IM 360 in central rack for connection of max. 3 expansion racks, with C-bus

Input current	
from backplane bus 5 V DC, max.	350 mA
Power loss	
Power loss, typ.	2 W
Hardware configuration	
Number of interfaces per CPU, max.	1
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	225 g

Classifications

	Version	Classification
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

EG-Konf. UK CA UL RCM EAC

Manufacturer Declaration

Subject to change without notice
© Copyright Siemens

EMV	For use in hazardous locations

RCM ATEX FM UL IECEx ATEX

For use in hazardous locations		Maritime application

Miscellaneous CCC-Ex

ABS BUREAU VERITAS DNV LRS

Maritime application

NK / Nippon Kaiji Kyokai PRS RINA CCS (China Classification Society)

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens