SIEMENS

Data sheet 6GK5332-0GA01-2AC2



SCALANCE XCM332 managed Layer 2 IE switch, 32x 10/100/1000 Mbit/s RJ45, LED diagnostics, error-signaling contact with select/set pushbutton, PROFINET IO device, network management, redundancy functions, office features (RSTP, VLAN, IGMP,..), CLP included in scope of supply assembly: DIN rail/S7 mounting rail .

product type designation	
product brand name	SCALANCE
product type designation	XCM332
Technical Product Detail Page	https://i.siemens.com/1P6GK5332-0GA01-2AC2
transfer rate	
transfer rate	10, 100, 1000 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	32; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
● with securing collar	32
interfaces / other	
number of electrical connections	
● for operator console	1
● for signaling contact	1
● for power supply	1
type of electrical connection	
● for operator console	USB (2.0 type B, USB-to-serial adapter)
● for signaling contact	2-pole terminal block
● for power supply	2 x 2-pole terminal block
number of extender expansion interfaces	1
design of the removable storage	
● CLP	Yes
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	43.2 W
● power loss [W] / at DC / at 24 V / typical	25.92 W
● supply voltage / 1 / voltage range	19.2 ... 28.8
● consumed current / 1 / maximum	1.8 A
● consumed current / at DC / at 24 V / typical	1.08 A
● type of electrical connection / 1 / for power supply	2 x 2-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	F 10 A / 250 V

Subject to change without notice
© Copyright Siemens

ambient conditions	
ambient temperature	
● during operation	-40 ... +60 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
operating condition / fanless operation	Yes
protection class IP	IP20
design, dimensions and weights	
design	compact
width	210 mm
height	147 mm
depth	125 mm
net weight	2.04 kg
fastening method	
● 19-inch installation	No
● 35 mm DIN-rail mounting	Yes
● wall mounting	Yes
● S7-300 rail mounting	Yes
● S7-1500 rail mounting	Yes
product features, product functions, product components / general	
product conformity / according to IEEE 802.1Qbu and IEEE 802.3br (Frame Preemption)	Yes
product license	
product license / Upgrade license	Yes; layer 3 license
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	No
● port mirroring	Yes
● multiport mirroring	Yes
● Encapsulated Remote Traffic Mirroring (ERTM)	Yes
● CoS	Yes
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B
network load class / according to PROFINET	II
telegram length / for Ethernet / maximum	9194 byte
protocol / is supported	
● Telnet	No
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● FTP	Yes
● SFTP	Yes
● BOOTP	No
● NETCONF	Yes
● GMRP	Yes
● DCP	Yes
● LLDP	Yes
● EtherNet/IP	Yes
● SNMP v1	Yes
● SNMP v2	Yes

Subject to change without notice
© Copyright Siemens

● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
product functions / VLAN	
product function	
● VLAN - port based	Yes
● VLAN - protocol-based	No
● VLAN - IP-based	No
● VLAN dynamic	Yes
number of VLANs / maximum	2048
number of VLANs - dynamic / maximum	2048
product functions / DHCP	
product function	
● DHCP server	No
● DHCP client	Yes
● DHCP Option 82	No
● DHCP Option 66	Yes
● DHCP Option 67	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● Media Redundancy Protocol Interconnection (MRP-I)	No
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	No
● high speed redundancy protocol (HRP) with standby redundancy	No
● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure RSTP+	No
● redundancy procedure MSTP	Yes
● passive listening	Yes
● eRSTP	Yes
protocol / is supported	
● LACP	Yes
product functions / security	
protocol / is supported	
● SSH	Yes
● SSL	Yes
product functions / time	
product function	
● SICLOCK support	Yes
● NTP-client	Yes
● IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
● NTP	Yes
● IEEE 1588 profile default	Yes
standards, specifications, approvals	

Subject to change without notice
© Copyright Siemens

certificate of suitability	
● CE marking	Yes
● UKCA marking	Yes
● cULus approval	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
● for EMC interference emission	EN 61000-6-4
● for immunity to EMC	EN 61000-6-2
● for safety / from CSA and UL	UL-61010-2 E85972
standards, specifications, approvals / hazardous environments	
certificate of suitability	
● ATEX	Yes
● UKEX	Yes
● IECEx	Yes
● ULhazloc approval	Yes
● CCC / for hazardous zone according to GB standard	Yes
● FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
● railway application in accordance with EN 50121-4	Yes; use only in areas not accessible to the public
● railway application in accordance with EN 50125-3	Yes; Section 4.2: Class AX (up to 2000m); section 4.3: T1: Containers N.T.C and T.C. / Buildings N.C.C and C.C, T2: Containers N.T.C and T.C. / Buildings N.C.C and C.C, TX: Containers N.T.C and T.C. / Buildings N.C.C and C.C., derating according to the manual must be observed when SFP/SFP+ transceivers are used --> only for variants with optical connections; In addition, depending on the installation position, the derating according to the manual must be taken into account; section 4.4: T1: Containers C.C. / Buildings N.C.C and C.C., T2: Containers C.C. / Buildings N.C.C and C.C, T3: Containers C.C. / Buildings N.C.C and C.C; section 4.11: C1: Indoor, C2: Indoor (except condensation), C3: Indoor (except condensation), 4B1, 4S10, UL 61010-2-10; section 4.13: partially, Test Fc: Vibration EN 60068-2-6; IEC 60068-2-6, Test Ea: Shock EN 60068-2-27; IEC 60068-2-27, Test Ec: Rough handling, shocks EN 60068-2-31; IEC 60068-2-31; section 4.14: yes; section 4.15: yes, according to manual.
● RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	1244.435 kg
● during manufacturing	123 kg
● during operation	1120 kg
● after end of life	0.908 kg
product functions / general	
MTBF	11.6 a
warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions

Subject to change without notice
© Copyright Siemens

	that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

Environmental Product Declaration

● global warming potential [CO2 eq] / during manufacturing	123 kg
● global warming potential [CO2 eq] / during sales	0.527 kg
● global warming potential [CO2 eq] / during operation	1120 kg
● global warming potential [CO2 eq] / after end of life	0.908 kg
● global warming potential [CO2 eq] / total	1244.435 kg

Environment	General Product Approval				
EPD	EG-Konf.	UL	RCM	TUEV	EG-Konf.

General Product Approval		For use in hazardous locations			
UKCA	China RoHS	ATEX	IECEx	FM	CCC-Ex

For use in hazardous locations	Test Certificates	Industrial Communication
UL	Type Test Certificates/Test Report	PROFINET

last modified: 8/28/2026

Subject to change without notice
© Copyright Siemens