SIEMENS

## Data sheet 6GK5524-8GS00-2AR2

SCALANCE XR524-8C; managed IE switch; layer 3 with Key-Plug available; Power supply 24 V DC; 24x 10/100/1000 Mbit/s RJ45; 8x 100/1000 Mbit/s SFP; contains 8 combo ports; in total 24 ports can be used; error signaling contact; select/set pushbutton; PROFINET IO device; redundancy functions; Office features (RSTP, VLAN, IGMP, ...); C-PLUG in scope of supply.



| | |
|---|---|
| **product type designation** | |
| product brand name | SCALANCE |
| product type designation | XR524-8C |
| Technical Product Detail Page | https://i.siemens.com/1P6GK5524-8GS00-2AR2 |
| **transfer rate** | |
| transfer rate | 10, 100, 1000 Mbit/s |
| **interfaces / for communication / integrated** | |
| number of electrical connections | |
| ● for network components or terminal equipment | 24; RJ45 |
| number of 100 Mbit/s ST(BFOC) ports | |
| ● for multimode | 0 |
| number of electrical connections | |
| ● for SFP | 8 |
| number of combo ports / with RJ45 interface for optical plug-in transceiver | 8 |
| **interfaces / for communication / plug-in** | |
| number of electrical connections | |
| ● for SFP | 8 |
| **interfaces / other** | |
| number of electrical connections | |
| ● for operator console | 1 |
| ● for signaling contact | 1 |
| ● for power supply | 1 |
| type of electrical connection | |
| ● for operator console | RJ11 |
| ● for management purposes | RJ45 |
| ● for signaling contact | 2-pole terminal block |
| ● for power supply | 4-pole terminal block |
| product feature / hot-swappable interface modules | Yes |
| operating voltage / of the signaling contacts | |
| ● at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| ● at DC / maximum | 0.1 A |
| **supply voltage, current consumption, power loss** | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage supply / redundant power supply unit | No |
| **type of voltage / 1 / of the supply voltage** | DC |
| ● supply voltage / 1 / rated value | 24 V |
| ● power loss [W] / 1 / rated value | 24 W |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● supply voltage / 1 / voltage range | 19.2 ... 28.8 |
| ● consumed current / 1 / maximum | 1 A |
| ● type of electrical connection / 1 / for power supply | 4-pole terminal block |
| ● product component / 1 / fusing at power supply input | Yes |
| ● fuse protection type / 1 / at input for supply voltage | 3,15 A / 125 V |
| **ambient conditions** | |
| ambient temperature | |
| ● during operation | -40 ... +70 °C |
| ● during storage | -40 ... +85 °C |
| ● during transport | -40 ... +85 °C |
| relative humidity | |
| ● at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| **design, dimensions and weights** | |
| design | 19-inch rack |
| number of modular height units / relating to 19-inch cabinet | 1 |
| width | 449 mm |
| height | 44 mm |
| depth | 305 mm |
| net weight | 3.8 kg |
| fastening method | |
| ● 19-inch installation | Yes |
| ● 35 mm DIN-rail mounting | No |
| ● wall mounting | No |
| ● S7-300 rail mounting | No |
| ● S7-1500 rail mounting | No |
| type of cable outlet | Cable outlet at front |
| **product features, product functions, product components / general** | |
| cascading in cases of star topology | any (depending only on signal propagation time) |
| **product functions / management, configuration, engineering** | |
| product function | |
| ● CLI | Yes |
| ● web-based management | Yes |
| ● MIB support | Yes |
| ● TRAPs via email | Yes |
| ● configuration with STEP 7 | Yes |
| ● RMON | Yes |
| ● port mirroring | Yes |
| ● multiport mirroring | Yes |
| ● CoS | Yes |
| ● PROFINET IO diagnosis | Yes |
| ● switch-managed | Yes |
| PROFINET conformity class | B |
| telegram length / for Ethernet / maximum | 9216 byte |
| protocol / is supported | |
| ● Telnet | Yes |
| ● HTTP | Yes |
| ● HTTPS | Yes |
| ● TFTP | Yes |
| ● FTP | Yes |
| ● BOOTP | Yes |
| ● GMRP | Yes |
| ● DCP | Yes |
| ● LLDP | Yes |
| ● SNMP v1 | Yes |
| ● SNMP v2 | Yes |
| ● SNMP v3 | Yes |
| ● IGMP (snooping/querier) | Yes |


© Copyright Siemens

| | |
|---|---|
| identification & maintenance function | |
| ● I&M0 - device-specific information | Yes |
| ● I&M1 - higher level designation/location designation | Yes |
| **product functions / diagnostics** | |
| product function | |
| ● port diagnostics | Yes |
| ● statistics Packet Size | Yes |
| ● statistics packet type | Yes |
| ● error statistics | Yes |
| ● SysLog | Yes |
| **product functions / VLAN** | |
| product function | |
| ● VLAN - port based | Yes |
| ● VLAN - protocol-based | Yes |
| ● VLAN - IP-based | Yes |
| ● VLAN dynamic | Yes |
| number of VLANs / maximum | 255 |
| number of VLANs - dynamic / maximum | 255 |
| **product functions / DHCP** | |
| product function | |
| ● DHCP client | Yes |
| ● DHCP Option 82 | Yes |
| ● DHCP Option 66 | Yes |
| ● DHCP Option 67 | Yes |
| **product functions / routing** | |
| service / routing / note | IP routing in combination with KEY-PLUG XR-500 |
| product function | |
| ● static IP routing | Yes |
| ● static IP routing IPv6 | Yes |
| ● dynamic IP routing | Yes |
| ● dynamic IP routing IPv6 | Yes |
| protocol / is supported | |
| ● RIPv2 | Yes |
| ● RIPnG for IPv6 | Yes |
| ● OSPFv2 | Yes |
| ● OSPFv3 for IPv6 | Yes |
| ● VRRP | Yes |
| ● VRRP for IPv6 | Yes |
| **product functions / redundancy** | |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| ● media redundancy protocol (MRP) with redundancy manager | Yes |
| ● Media Redundancy Protocol Interconnection (MRP-I) | Yes; LC mode |
| ● ring redundancy | Yes |
| ● high speed redundancy protocol (HRP) with redundancy manager | Yes |
| ● high speed redundancy protocol (HRP) with standby redundancy | Yes |
| ● redundancy procedure STP | Yes |
| ● redundancy procedure RSTP | Yes |
| ● redundancy procedure RSTP+ | Yes |
| ● redundancy procedure MSTP | Yes |
| ● passive listening | Yes |
| protocol / is supported | |
| ● LACP | Yes |
| **product functions / security** | |
| product function | |
| ● IEEE 802.1x (radius) | Yes |


© Copyright Siemens

| | |
|---|---|
| ● broadcast/multicast/unicast limiter | Yes |
| ● broadcast blocking | Yes |
| protocol / is supported | |
| ● SSH | Yes |
| **product functions / time** | |
| product function | |
| ● SICLOCK support | Yes |
| protocol / is supported | |
| ● NTP | Yes |
| ● SNTP | Yes |
| **standards, specifications, approvals** | |
| certificate of suitability | |
| ● CE marking | Yes |
| ● KC approval | Yes |
| ● Regulatory Compliance Mark (RCM) | Yes |
| standard | |
| ● for EMC interference emission | EN 61000-6-4 (Class A) |
| ● for immunity to EMC | EN 61000-6-2 |
| ● for safety / from CSA and UL | UL 60950-1; CSA C22.2 No. 213-M1987 |
| **standards, specifications, approvals / hazardous environments** | |
| certificate of suitability | |
| ● ATEX | Yes |
| ● UKEX | Yes |
| ● IECEx | Yes |
| ● ULhazloc approval | Yes |
| ● CCC / for hazardous zone according to GB standard | Yes |
| ● FM registration | Yes |
| **standards, specifications, approvals / other** | |
| certificate of suitability | |
| ● RoHS conformity | Yes |
| resistance to air pollution / conformity according to ANSI/ISA-71.04 | Yes; G3 |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019 | Yes |
| **standards, specifications, approvals / marine classification** | |
| Marine classification association | |
| ● Royal Institution of Naval Architects (RINA) | Yes |
| **standards, specifications, approvals / Environmental Product Declaration** | |
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| ● total | 802.05 kg |
| ● during manufacturing | 132 kg |
| ● during operation | 669.46 kg |
| ● after end of life | 0.59 kg |
| **product functions / general** | |
| warranty period | 5 a |
| **further information / internet links** | |
| internet link | |
| ● to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| ● to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| ● to website: Industrial communication | https://www.siemens.com/simatic-net |
| ● to web page: SiePortal | https://sieportal.siemens.com/ |
| ● to website: Image database | https://www.automation.siemens.com/bilddb |
| ● to website: CAx-Download-Manager | https://www.siemens.com/cax |
| ● to website: Industry Online Support | https://support.industry.siemens.com |
| **security information** | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, |


© Copyright Siemens

| | |
|---|---|
| | state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7) |

## Approvals / Certificates

### Environmental Product Declaration

| | |
|---|---|
| ● global warming potential [CO2 eq] / during manufacturing | 132 kg |
| ● global warming potential [CO2 eq] / during operation | 669.46 kg |
| ● global warming potential [CO2 eq] / after end of life | 0.59 kg |
| ● global warming potential [CO2 eq] / total | 802.05 kg |

**Environment** | **General Product Approval**

EPD | CE EG-Konf. | Declaration of Conformity | EAC | China RoHS | Manufacturer Declaration

**General Product Approval** | **EMV**

Special Test Certificate | RCM | CE EG-Konf. | China RoHS | UKCA | KC

**For use in hazardous locations** | **Maritime application**

IECEx | ATEX | FM | CCC-Ex | ABS | BUREAU VERITAS

**Maritime application** | **Industrial Communication**

DNV | LRS | NK / Nippon Kaiji Kyokai | PRS | RINA | PROFINET

**last modified:** 8/28/2026


Subject to change without notice
© Copyright Siemens